

CA Solar LLC

LED Tube Lighting (T8)

**Energy efficient, environmental friendly products that last up to 10 years.
Make retrofit and No more frequent lamp replacement.
Payback time in as less as 2 years.**



Features

- Designed as a direct retrofit into most fluorescent lamp fixture using existing sockets (requires line voltage to bypass ballast/transformer/starter)
- Energy efficiency: Saving up to 65% than traditional incandescent lamp.
- Long life: Up to 50,000 hours & 10 times longer than incandescent lamp.
- No UV light, no stroboflash, & soft light: Good & comfort for human eyes.
- Environmental Friendly: No mercury, no lead material used in the products.
- Low Maintenance: Saving labor of frequent lamp replacement.
- RoHS and CE complaint. 5 year limited product warranty.
- Best for using in retail stores, hotels, restaurants, offices, exhibition hall, public transportation stations, government buildings, factories and warehouses, etc.

Specifications

Item No.	power	Voltage	Luminous Flux	Luminous Intensity	Color Temperature	Led Q'ty	Material	Dimension	Replacing Fluorescent
Dip Series									
D8-5W	5W	AC85-285V	396 lm	94 lux	3000-6500K	72	Al + PC	∅ 26× 344mm	15W
D8-8w	8w	AC85-285V	792 lm	130 lux	3000-6500K	144	Al + PC	∅ 26× 602mm	20W
D8-10w	10w	AC85-285V	1040 lm	177 lux	3000-6500K	189	Al + PC	∅ 26× 906mm	30W
D8-12w	12w	AC85-285V	1201 lm	201 lux	3000-6500K	216	Al + PC	∅ 26× 1212mm	35W
D8-15w	15w	AC85-285V	1496 lm	245 lux	3000-6500K	276	Al + PC	∅ 26× 1212mm	40W
D8-18w	18w	AC85-285V	1768 lm	255 lux	3000-6500K	330	Al + PC	∅ 26× 1212mm	----
D8-22w	22w	AC85-285V	2112 lm	362 lux	3000-6500K	384	Al + PC	∅ 26× 1212mm	----
D8-25w	25w	AC85-285V	2380 lm	403 lux	3000-6500K	432	Al + PC	∅ 26× 1512mm	----
D8-33w	33w	AC85-285V	3300 lm	417 lux	3000-6500K	600	Al + PC	∅ 26× 2382mm	----
SMD Series									
S8-5W	5W	AC85-285V	396 lm	94 lux	3000-6500K	72	Al + PC	∅ 26× 344mm	15W
S8-8w	8w	AC85-285V	792 lm	130 lux	3000-6500K	144	Al + PC	∅ 26× 602mm	20W
S8-10w	10w	AC85-285V	1040 lm	177 lux	3000-6500K	189	Al + PC	∅ 26× 906mm	30W
S8-12w	12w	AC85-285V	1201 lm	201 lux	3000-6500K	216	Al + PC	∅ 26× 1212mm	35W
S8-15w	15w	AC85-285V	1496 lm	245 lux	3000-6500K	276	Al + PC	∅ 26× 1212mm	40W
S8-18w	18w	AC85-285V	1768 lm	255 lux	3000-6500K	330	Al + PC	∅ 26× 1212mm	----
S8-22w	22w	AC85-285V	2112 lm	362 lux	3000-6500K	384	Al + PC	∅ 26× 1212mm	----
S8-25w	25w	AC85-285V	2380 lm	403 lux	3000-6500K	432	Al + PC	∅ 26× 1512mm	----
S8-33w	33w	AC85-285V	3300 lm	417 lux	3000-6500K	600	Al + PC	∅ 26× 2382mm	----



For more information, please contact

CA Solar LLC, 33442 Western Ave., Union City, California

Email: sales@casolarco.com; Tel: +1.510.380.8899; Website: www.casolarco.com